

ENGINE SPEED (rpm):	1800	RATING STRATEGY:	STANDARD
COMPRESSION RATIO:	11:1	FUEL:	Nat Gas
AFTERCOOLER TYPE:	SCAC	FUEL SYSTEM:	CAT LOW PRESSURE
AFTERCOOLER - STAGE 2 INLET (°F):	130		WITH AIR FUEL RATIO CONTROL
AFTERCOOLER - STAGE 1 INLET (°F):	192	FUEL PRESSURE RANGE(psig):	1.5-5.0
JACKET WATER OUTLET (°F):	198	FUEL METHANE NUMBER:	80
ASPIRATION:	TA	FUEL LHV (Btu/scf):	905
COOLING SYSTEM:	JW+OC+1AC, 2AC	ALTITUDE CAPABILITY AT 77°F INLET AIR TEMP. (ft):	2238
CONTROL SYSTEM:	ADEM3	APPLICATION:	Genset
EXHAUST MANIFOLD:	DRY	POWER FACTOR:	0.8
COMBUSTION:	Low Emission	VOLTAGE(V):	380-4160
NOx EMISSION LEVEL (g/bhp-hr NOx):	0.5		

RATING		NOTES	LOAD	100%	75%	50%
GENSET POWER	(WITHOUT FAN)	(1)(2)	ekW	1300	975	650
GENSET POWER	(WITHOUT FAN)	(1)(2)	kVA	1625	1218	812
ENGINE POWER	(WITHOUT FAN)	(2)	bhp	1818	1364	910
GENERATOR EFFICIENCY		(1)	%	95.9	95.8	95.8
GENSET EFFICIENCY(@ 1.0 Power Factor)	(ISO 3046/1)	(3)	%	34.7	33.2	31.1
THERMAL EFFICIENCY		(4)	%	50.8	52.3	54.5
TOTAL EFFICIENCY (@ 1.0 Power Factor)		(5)	%	85.5	85.5	85.6

ENGINE DATA						
GENSET FUEL CONSUMPTION	(ISO 3046/1)	(6)	Btu/ekW-hr	9965	10415	11036
GENSET FUEL CONSUMPTION	(NOMINAL)	(6)	Btu/ekW-hr	10158	10618	11250
ENGINE FUEL CONSUMPTION	(NOMINAL)	(6)	Btu/bhp-hr	7261	7589	8037
AIR FLOW (77°F, 14.7 psia)	(WET)	(7)	ft ³ /min	4121	3172	2188
AIR FLOW	(WET)	(7)	lb/hr	18272	14067	9702
FUEL FLOW (60°F, 14.7 psia)			scfm	243	191	135
COMPRESSOR OUT PRESSURE			in Hg(abs)	87.4	82.5	60.2
COMPRESSOR OUT TEMPERATURE			°F	345	326	234
AFTERCOOLER AIR OUT TEMPERATURE			°F	129	130	130
INLET MAN. PRESSURE		(8)	in Hg(abs)	79.9	62.9	43.8
INLET MAN. TEMPERATURE	(MEASURED IN PLENUM)	(9)	°F	139	140	140
TIMING		(10)	°BTDC	22	22	22
EXHAUST TEMPERATURE - ENGINE OUTLET		(11)	°F	974	985	1009
EXHAUST GAS FLOW (@engine outlet temp, 14.5 psia)	(WET)	(12)	ft ³ /min	11850	9202	6461
EXHAUST GAS MASS FLOW	(WET)	(12)	lb/hr	18939	14590	10072
MAX INLET RESTRICTION		(13)	in H ₂ O	10.04	7.99	3.98
MAX EXHAUST RESTRICTION		(13)	in H ₂ O	20.07	12.41	5.51

EMISSIONS DATA - ENGINE OUT						
NOx (as NO ₂)		(14)(15)	g/bhp-hr	0.50	0.50	0.50
CO		(14)(16)	g/bhp-hr	2.49	2.58	2.82
THC (mol. wt. of 15.84)		(14)(16)	g/bhp-hr	5.45	5.82	6.78
NMHC (mol. wt. of 15.84)		(14)(16)	g/bhp-hr	0.82	0.87	1.02
NMNEHC (VOCs) (mol. wt. of 15.84)		(14)(16)(17)	g/bhp-hr	0.54	0.58	0.68
HCHO (Formaldehyde)		(14)(16)	g/bhp-hr	0.34	0.37	0.42
CO ₂		(14)(16)	g/bhp-hr	504	527	559
EXHAUST OXYGEN		(14)(18)	% DRY	9.3	9.1	9.0
LAMBDA		(14)(18)		1.73	1.70	1.66

ENERGY BALANCE DATA						
LHV INPUT		(19)	Btu/min	220051	172501	121849
HEAT REJECTION TO JACKET WATER (JW)		(20)(28)	Btu/min	28688	25137	21558
HEAT REJECTION TO ATMOSPHERE		(21)	Btu/min	7365	6138	4912
HEAT REJECTION TO LUBE OIL (OC)		(22)(28)	Btu/min	7401	6761	5967
HEAT REJECTION TO EXHAUST (LHV TO 77°F)		(23)(24)	Btu/min	81165	63518	45440
HEAT REJECTION TO EXHAUST (LHV TO 248°F)		(23)	Btu/min	61754	48372	34572
HEAT REJECTION TO A/C - STAGE 1 (1AC)		(25)(28)	Btu/min	9380	6325	1345
HEAT REJECTION TO A/C - STAGE 2 (2AC)		(26)(29)	Btu/min	7961	5809	3073
PUMP POWER		(27)	Btu/min	977	977	977

CONDITIONS AND DEFINITIONS

Engine rating obtained and presented in accordance with ISO 3046/1. (Standard reference conditions of 77°F, 29.60 in Hg barometric pressure.) No overload permitted at rating shown. Consult the altitude deration factor chart for applications that exceed the rated altitude or temperature.

Emission levels are at engine exhaust flange prior to any after treatment. Values are based on engine operating at steady state conditions, adjusted to the specified NOx level at 100% load. Tolerances specified are dependent upon fuel quality. Fuel methane number cannot vary more than ± 3.

For notes information consult page three.

FUEL USAGE GUIDE

CAT METHANE NUMBER	30	35	40	45	50	55	60	65	70	75	80	100
SET POINT TIMING	-	-	-	-	-	-	22	21	20	21	22	22
DERATION FACTOR	0	0	0	0	0	0	0.84	0.92	1	1	1	1

ALTITUDE DERATION FACTORS AT RATED SPEED

INLET AIR TEMP °F	ALTITUDE (FEET ABOVE SEA LEVEL)												
	0	1000	2000	3000	4000	5000	6000	7000	8000	9000	10000	11000	12000
130	0.99	0.95	0.92	0.88	0.85	0.82	0.79	0.76	0.73	0.70	0.67	0.64	0.62
120	1	0.97	0.93	0.90	0.87	0.83	0.80	0.77	0.74	0.71	0.68	0.65	0.63
110	1	0.99	0.95	0.92	0.88	0.85	0.81	0.78	0.75	0.72	0.69	0.67	0.64
100	1	1	0.97	0.93	0.90	0.86	0.83	0.80	0.77	0.74	0.71	0.68	0.65
90	1	1	0.99	0.95	0.91	0.88	0.84	0.81	0.78	0.75	0.72	0.69	0.66
80	1	1	1	0.97	0.93	0.89	0.86	0.83	0.79	0.76	0.73	0.70	0.67
70	1	1	1	0.98	0.95	0.91	0.88	0.84	0.81	0.78	0.75	0.72	0.69
60	1	1	1	1	0.97	0.93	0.89	0.86	0.82	0.79	0.76	0.73	0.70
50	1	1	1	1	0.98	0.95	0.91	0.87	0.84	0.81	0.78	0.74	0.71

AFTERCOOLER HEAT REJECTION FACTORS (ACHRF)

INLET AIR TEMP °F	ALTITUDE (FEET ABOVE SEA LEVEL)												
	0	1000	2000	3000	4000	5000	6000	7000	8000	9000	10000	11000	12000
130	1.34	1.39	1.45	1.46	1.46	1.46	1.46	1.46	1.46	1.46	1.46	1.46	1.46
120	1.27	1.32	1.38	1.39	1.39	1.39	1.39	1.39	1.39	1.39	1.39	1.39	1.39
110	1.20	1.25	1.31	1.32	1.32	1.32	1.32	1.32	1.32	1.32	1.32	1.32	1.32
100	1.13	1.18	1.24	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25
90	1.06	1.11	1.17	1.18	1.18	1.18	1.18	1.18	1.18	1.18	1.18	1.18	1.18
80	1	1.05	1.09	1.11	1.11	1.11	1.11	1.11	1.11	1.11	1.11	1.11	1.11
70	1	1	1.02	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04
60	1	1	1	1	1	1	1	1	1	1	1	1	1
50	1	1	1	1	1	1	1	1	1	1	1	1	1

FUEL USAGE GUIDE:

This table shows the derate factor and full load set point timing required for a given fuel. Note that deration and set point timing reduction may be required as the methane number decreases. Methane number is a scale to measure detonation characteristics of various fuels. The methane number of a fuel is determined by using the Caterpillar methane number calculation program.

ALTITUDE DERATION FACTORS:

This table shows the deration required for various air inlet temperatures and altitudes. Use this information along with the fuel usage guide chart to help determine actual engine power for your site.

ACTUAL ENGINE RATING:

To determine the actual rating of the engine at site conditions, one must consider separately, limitations due to fuel characteristics and air system limitations. The Fuel Usage Guide deration establishes fuel limitations. The Altitude/Temperature deration factors and RPC (reference the Caterpillar Methane Program) establish air system limitations. RPC comes into play when the Altitude/Temperature deration is less than 1.0 (100%). Under this condition, add the two factors together. When the site conditions do not require an Altitude/Temperature derate (factor is 1.0), it is assumed the turbocharger has sufficient capability to overcome the low fuel relative power, and RPC is ignored. To determine the actual power available, take the lowest rating between 1) and 2).

- 1) Fuel Usage Guide Deration
- 2) $1 - ((1 - \text{Altitude/Temperature Deration}) + (1 - \text{RPC}))$

AFTERCOOLER HEAT REJECTION FACTORS(ACHRF):

To maintain a constant air inlet manifold temperature, as the inlet air temperature goes up, so must the heat rejection. As altitude increases, the turbocharger must work harder to overcome the lower atmospheric pressure. This increases the amount of heat that must be removed from the inlet air by the aftercooler. Use the aftercooler heat rejection factor (ACHRF) to adjust for inlet air temp and altitude conditions. See notes 28 and 29 for application of this factor in calculating the heat exchanger sizing criteria. Failure to properly account for these factors could result in detonation and cause the engine to shutdown or fail.

INLET AND EXHAUST RESTRICTIONS FOR ALTITUDE CAPABILITY:

The altitude derate chart is based on the maximum inlet and exhaust restrictions provided on page 1. Contact factory for restrictions over the specified values. Heavy Derates for higher restrictions will apply.

NOTES:

1. Generator efficiencies, power factor, and voltage are based on standard generator. [Genset Power (ekW) is calculated as: Engine Power (bkW) x Generator Efficiency], [Genset Power (kVA) is calculated as: Engine Power (bkW) x Generator Efficiency / Power Factor]
2. Rating is with two engine driven water pumps. Tolerance is (+)3, (-)0% of full load.
3. ISO 3046/1 Genset efficiency tolerance is (+)0, (-)5% of full load % efficiency value based on a 1.0 power factor.
4. Thermal Efficiency is calculated based on energy recovery from the jacket water, lube oil, 1st stage aftercooler, and exhaust to 248°F with engine operation at ISO 3046/1 Genset Efficiency, and assumes unburned fuel is converted in an oxidation catalyst.
5. Total efficiency is calculated as: Genset Efficiency + Thermal Efficiency. Tolerance is $\pm 10\%$ of full load data.
6. ISO 3046/1 Genset fuel consumption tolerance is (+)5, (-)0% of full load data. Nominal genset and engine fuel consumption tolerance is $\pm 3.0\%$ of full load data.
7. Air flow value is on a 'wet' basis. Flow is a nominal value with a tolerance of $\pm 5\%$.
8. Inlet manifold pressure is a nominal value with a tolerance of $\pm 5\%$.
9. Inlet manifold temperature is a nominal value with a tolerance of $\pm 9^\circ\text{F}$.
10. Timing indicated is for use with the minimum fuel methane number specified. Consult the appropriate fuel usage guide for timing at other methane numbers.
11. Exhaust temperature is a nominal value with a tolerance of (+)63°F, (-)54°F.
12. Exhaust flow value is on a 'wet' basis. Flow is a nominal value with a tolerance of $\pm 6\%$.
13. Inlet and Exhaust Restrictions are maximum allowed values at the corresponding loads. Increasing restrictions beyond what is specified will result in a significant engine derate.
14. Emissions data is at engine exhaust flange prior to any after treatment.
15. NOx tolerances are $\pm 18\%$ of specified value.
16. CO, CO₂, THC, NMHC, NMNEHC, and HCHO values are "Not to Exceed" levels. THC, NMHC, and NMNEHC do not include aldehydes.
17. VOCs - Volatile organic compounds as defined in US EPA 40 CFR 60, subpart JJJJ
18. Exhaust Oxygen tolerance is ± 0.5 ; Lambda tolerance is ± 0.05 . Lambda and Exhaust Oxygen level are the result of adjusting the engine to operate at the specified NOx level.
19. LHV rate tolerance is $\pm 3.0\%$.
20. Heat rejection to jacket water value displayed includes heat to jacket water alone. Value is based on treated water. Tolerance is $\pm 10\%$ of full load data.
21. Heat rejection to atmosphere based on treated water. Tolerance is $\pm 50\%$ of full load data.
22. Lube oil heat rate based on treated water. Tolerance is $\pm 20\%$ of full load data.
23. Exhaust heat rate based on treated water. Tolerance is $\pm 10\%$ of full load data.
24. Heat rejection to exhaust (LHV to 77°F) value shown includes unburned fuel and is not intended to be used for sizing or recovery calculations.
25. Heat rejection to A/C - Stage 1 based on treated water. Tolerance is $\pm 5\%$ of full load data.
26. Heat rejection to A/C - Stage 2 based on treated water. Tolerance is $\pm 5\%$ of full load data.
27. Total Jacket Water Circuit heat rejection is calculated as: $(\text{JW} \times 1.1) + (\text{OC} \times 1.2) + (1\text{AC} \times 1.05) + [0.764 \times (1\text{AC} + 2\text{AC}) \times (\text{ACHRF} - 1) \times 1.05]$. Heat exchanger sizing criterion is maximum circuit heat rejection at site conditions, with applied tolerances. A cooling system safety factor may be multiplied by the total circuit heat rejection to provide additional margin.
28. Total Second Stage Aftercooler Circuit heat rejection is calculated as: $(2\text{AC} \times 1.05) + [(1\text{AC} + 2\text{AC}) \times 0.236 \times (\text{ACHRF} - 1) \times 1.05]$. Heat exchanger sizing criterion is maximum circuit heat rejection at site conditions, with applied tolerances. A cooling system safety factor may be multiplied by the total circuit heat rejection to provide additional margin.

ENGINE POWER (bhp):	1818	COOLING SYSTEM:	JW+OC+1AC, 2AC
ENGINE SPEED (rpm):	1800	JACKET WATER OUTLET (°F):	198
EXHAUST MANIFOLD:	DRY		

Free Field Mechanical and Exhaust Noise

SOUND PRESSURE LEVEL (dB)											
Octave Band Center Frequency (OBCF)											
100% Load Data		dB(A)	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Mechanical Sound	Distance from the Engine (ft)	3.3	109.3	64.7	81.4	87.8	94.9	98.1	95.4	93.9	105.2
		23.0	92.4	47.8	64.5	70.9	78	81.2	78.5	77	88.3
		49.2	85.8	41.2	57.9	64.3	71.4	74.6	71.9	70.4	81.7
Exhaust Sound	Distance from the Engine (ft)	4.9	112.1	70.5	105.3	90.6	92.1	91.7	98.5	100.2	99
		23.0	98.7	57.1	91.9	77.2	78.7	78.3	85.1	86.8	85.6
		49.2	92.1	50.5	85.3	70.6	72.1	81.7	78.5	80.2	79

SOUND PARAMETER DEFINITION:

Data Variability Statement:

Sound data presented by Caterpillar has been measured in accordance with ISO 6798 in a Grade 3 test environment. Measurements made in accordance with ISO 6798 will result in some amount of uncertainty. The uncertainties depend not only on the accuracies with which sound pressure levels and measurement surface areas are determined, but also on the 'near-field error' which increases for smaller measurement distances and lower frequencies. The uncertainty for a Grade 3 test environment, that has a source that produces sounds that are uniformly distributed in frequency over the frequency range of interest, is equal to 4 dB (A-weighted). This uncertainty is expressed as the largest value of the standard deviation.